



TECHNICAL DATA SHEET

Aramid & PTFE Combination Packing INMARCO STYLE 105

Description:

STYLE 105 is a dense braided combination gland packing having aramid yarn corners with PTFE yarn faces with highly resilient and high tensile core of aramid fibre. The aramid yarn is lubricated with highly anti-frictional fluoropolymer dispersions and break-in lubricant, while the PTFE faces are lubricated with high temperature resisting inert lubricant.

STYLE 105 offers excellent strength coupled with dimensional stability in service. Strong aramid fibre avoids corner failures in reciprocating plunger pump. The PTFE fibre ensures low friction, cool shaft runs eliminating wear and tear to plunger & valve stems. The strong aramid fiber core provides extremely high pressure resistance.

Operational Parameters:

PROPERTIES	(b)	\Leftrightarrow	Tol
рН	1-13		
TEMPERATURE (°C)	-200 to +280		
PRESSURE (BAR)	150	500	500
VELOCITY (m/s)	25	20	
SIZE	4mm² to 35mm²		

Typical Applications:

Centrifugal reciprocating & plunger pumps, Valves, Agitators, Extruders, Mixers, Reactors etc.

Service Media:

Ammonia, Urea & Carbamate condensate in fertilizer industry, Amide, Fine slurries, Detergents, Pigments, Dyestuffs, Paints, Emulsions, Synthetic molten material, Tri sodium phosphate, Hydrazine, Sodium hexameta phosphate, Water, etc.

Advantages:

- ❖ Dense construction & excellent sealability.
- High pressure & compatibility.
- Extremely durable packing for ammonia and carbamate solution.
- Can be used as lip seals.
- ❖ Wide chemical & abrasion resistance & high penetration.

All information and recommendations given in this technical data sheet are correct to the best of our knowledge. However, in view of the wide variety of application and operating conditions one cannot draw the final conclusion in all application cases regarding the behavior of compounds. The above information can only serve as a guideline.