

**TECHNICAL DATA SHEET**




## Bulk Gland Sealing Compound

### **STYLE INSEAL-GPL**

**Description:**

**INSEAL-GPL** a blend of chemical resistant fibrils, inert fibrils, inert lubrications and sealing aids. Available in cake & stick form.

**Operational Parameters:**

PROPERTIES			
pH		3-12	
TEMPERATURE (°C)		-240 to +260	
PRESSURE (BAR)		300	
VELOCITY (m/s)		30mtr/sec.	

**Advantages:**

- ❖ General purpose IN SITU sealing sticks for pumps, agitators, dryers, mixers & reaction vessels.

**Typical Applications:**

Hot & cold water, boiler feed, mild acids & alkalis, organic chemicals and low temperature steam.

All information and recommendations given in this technical data sheet are correct to the best of our knowledge. However, in view of the wide variety of application and operating conditions one cannot draw the final conclusion in all application cases regarding the behavior of compounds. The above information can only serve as a guideline.

INMARCO FZC

P.O. Box 120284, Sharjah Airport International Free Zone (SAIF-Zone), Sharjah, UAE

Tel. No.: +971 6 5578378 Fax No.: +971 6 5578948

Email: [info@inmarco.ae](mailto:info@inmarco.ae) Web.: [www.inmarco.ae](http://www.inmarco.ae)