



Innovations in Fluid Sealing






TECHNICAL DATA SHEET

BULK GLAND SEALING COMPOUND **STYLE INSEAL-CR**

Description:

INSEAL-CR a blend of high temperature inert fibrils, solid lubrications and sealing aids.

Operational Parameters:

PROPERTIES			
pH	0-14		
TEMPERATURE (°C)	-240 to +250		
PRESSURE (BAR)	400		
VELOCITY (m/s)	30mtr/sec.		

Advantages:

- ❖ High chemical resistant flexible IN SITU sealing sticks for pumps, valves, mixers, agitators, autoclaves, dryers, reaction vessels.

Typical Applications:

Aggressive chemical, acid & alkalis, volatile organic chemical, oils, boiler feed water, emissive gases, thermic fluids, ash slurries.

All information and recommendations given in this technical data sheet are correct to the best of our knowledge. However, in view of the wide variety of application and operating conditions one cannot draw the final conclusion in all application cases regarding the behavior of compounds. The above information can only serve as a guideline.

INMARCO FZC

P.O. Box 120284, Sharjah Airport International Free Zone (SAIF-Zone), Sharjah, UAE

Tel. No.: +971 6 5578378 Fax No.: +971 6 5578948

Email: info@inmarco.ae Web.: www.inmarco.ae